

BlueTraker LRIT

for Commercial Shipping



LRIT - Long Range Identification and Tracking

BlueTraker
by **eima**
WIRELESS DATA SOLUTIONS

BlueTraker LRIT



BlueTraker LRIT is **fully compliant with IMO regulations on Long Range Identification and Tracking (LRIT)** and is the leading terminal for integration in LRIT systems on the market.

It configures and transmits:

- Automatic Position Report (APR):
 - Identity of the ship.
 - Position of the ship.
 - Date and time of the position.
- On-demand position report polling.
- Pre-scheduled position reports.

Truly global communication coverage through the Iridium satellite network!

Absolutely free full pre-conformance test!

Full package with 50 m cable and mounting accessories!

BlueTraker LRIT offers **reliable, safe, and secure global LRIT operations** for all types of vessels. It is a cost-effective solution with a life-long operation. Its exceptional features and benefits are unparalleled.

Fully Integrated with Robust Design

BlueTraker LRIT is a fully integrated device with embedded GPS and Iridium antennas, removing any need to connect additional external components for tracking and monitoring. All its components are packed inside a very robust, double-shell housing with IP68 and IP69K environmental protection. This level of integration makes misapplication impossible and so protects sensitive 'cable rich' modular devices.

Free Full Pre-conformance Test

When installed on a ship, all LRIT terminals have to be tested for communication capabilities by an Application Service Provider (ASP) and acquire Conformance Test Report (CTR). In order to complete the test hassle, BlueTraker LRIT customers have the unique option of a full and absolutely free pre-conformance test with our engineers.

Pole-to-Pole Coverage and Optimized Running Cost

BlueTraker LRIT terminal offers a truly global communication coverage through the Iridium Low Earth Orbit (LEO) satellite constellation, which is the only one offering 100% Pole-to-Pole coverage, including sea area A4. The BlueTraker LRIT terminal transmits Automatic Position Reports (APR) using Iridium's efficient and cost-effective Short Burst Data (SBD) service.


A Complete Ship-Borne LRIT Solution

BlueTraker LRIT terminal is an easy-to-install device, installed above the deck and is able to withstand the harshest weather conditions. It comes together with a 50 m connection cable and all mounting accessories.

With the International Maritime Organization (IMO) resolution MSC.202(81) adoption of chapter V amendment of the International Convention for the Safety of Life at Sea (SOLAS), regulation 19-1, the LRIT regulation applies to: All passenger ships, including high-speed craft on international voyages; Cargo ships, including high-speed craft of 300 gross tonnages and above on international voyages; Mobile offshore drilling units.

The Long-Range Identification and Tracking (LRIT) system provides global identification and tracking of ships.

BlueTraker LRIT Arctic



Shorter routes between the Atlantic and the Pacific Ocean are opening up: Northern Sea Route [North East passage] through the Russian Arctic, and North West Passage through the Canadian Arctic.

Navigating these routes means navigating the A4 Sea Area, essentially North and South of about 70 degrees of latitude, and through the Arctic, where the Iridium satellite network is the only choice of communication, and all electronics are under stress due to extreme weather conditions.

Cold start at -50°C.

World's only LRIT terminal engineered to withstand the rigorous voyages in the Arctic!

Complete A4 Sea Area communication coverage through the Iridium satellite network!

All electronic and mechanical components are specially selected to operate in low temperatures!

Unparalleled Features and Advantages:

Reliable Operation

BlueTraker LRIT Arctic is certified for operating in temperatures down to -50°C. Integrated pre-heating element increases inner housing temperature. At the same time, it prevents the device temperature from dropping below -40°C when the outside temperature drops to -50°C!

Smart Engineering

All electronic components used in a BlueTraker LRIT Arctic are selected for operating in low-temperature range. Smart thermostatic temperature control enables successful "Cold Start" - important in cases of main power loss in extremely cold environments and then powering-up again.

Smart Firmware, specially designed for Arctic operations, provides safe thermostatic control to keep working in these extremely low temperatures.

Customizable Mounts and Various Accessories

Sturdy stainless steel (EN1.4571) is used for the mount and can withstand mechanical stress and vibration at temperatures down to -50°C. Arctic grade power supply cable ensures flexibility and reliable operation in extreme cold.

The Perfect Choice for the A4 Sea Area

BlueTraker LRIT Arctic is truly the world's only LRIT terminal that enables operation in the extremely cold environments of Arctic areas. It resists accelerated cooling in extreme environments, successfully battling the Arctic chill factor - the effect of the Arctic wind on exposed electronic equipment.

The Benchmark for A4 LRIT Operation

The BlueTraker LRIT Arctic terminal can operate in extremely cold environments with temperatures down to -50°C. It is the benchmark for LRIT operation under extreme conditions and was extensively tested by Intertek of Finland for Arctic operation.

BlueTraker LRIT Technical Specifications

External power supply	24 V DC, 1 A / Arctic version 9 V DC to 36 V DC, 0.5 A max
Power supply protection	Power line disconnects above 36 V Withstands continuous connection up to 150 V DC source Internal self recovering poly fuse
Operating temperature - Standard version	-25 °C to +55 °C
Operating temperature - Arctic version	-50 °C to +55 °C
Storage temperature	-40 °C to +70 °C
Waterproof and dust protection	IP68 protection class (depth 6 m, duration 30 mins.)
Integrated antennas	GPS, Iridium
Iridium transceiver	Frequency range 1616 MHz to 1626.5 MHz; Maximum output power +32 dBm (1.6 W)
GPS receiver	33 channels, 1 sec. update rate, 1575.42 MHz (L1 band) Accuracy: Position 5 m CEP, Velocity 0.1 m/sec Sensitivity: - 167 dBm tracking
Installation	External, mast, vertical rail, horizontal rail, flat vertical surface
Mounting accessories	UniMount mounting bracket (included)
Cable	50 m (included)
Housing	Double-shell, white-coloured outer shell, resistant to UV sun radiation
Mechanical	Dimensions: 198 x 67 x 198 mm (width x height x length) Weight: 1.19 kg; 2 kg with UniMount
Shock resistance	Multiple drop from 1.2 m height to every side of the device

Standards, Certificates and Type Approvals

- Iridium Compliance Certificate
- US Coast Guard Certificate
- DNV GL Type Approval
- Russian Maritime Register of Shipping Type Approval
- IEC60945 - Marine environment standards compliance
- IP68 & IP69K - Water and dust grade protection grade standards
- Quality management system certified: EN ISO 9001 & EN ISO 14001



U.S. Department of
Homeland Security
**United States
Coast Guard**



EMA d.o.o., Teharje 7B,
SI-3000 Celje, SLOVENIA, EU

+386 3 42 84 800

sales@bluetraker.com

www.bluetraker.com

©2023 EMA - Wireless Data Solutions
- All rights reserved.

Except otherwise noted, the reuse of this document or its part is authorized under a Creative Commons Attribution 4.0 (CC/BY 4.0) international license (<https://creativecommons.org/licenses/by/4.0/>). This means that reuse is allowed provided appropriate credit is given to EMA d.o.o. and any changes are indicated. For any use or reproduction of elements that are not owned by EMA d.o.o., permission may need to be sought directly from the respective rightsholders.

EMA reserves the right to make changes to products or specifications without prior notice. | All trademarks or registered trademarks are the property of their respective owners. | Part No: 10703 | Doc. Ver.: 6.2.4

Distributor Label

HERE